

INTERCHANGEABLE HEAD TORQUE WRENCHES

Interchangeable screen micrometer torque wrenches

Interchangeable head torque wrenches provide the convenience of choosing between a large selection of open-end, ring and ratchet heads.

Interchangeable heads can be purchased separately.

Features:

- Accuracy +/- 4%
- Left & right hand operation
- Interchangeable head
- Meets or exceeds international standards
- Metric scale
- Metric / imperial conversion printed on the body of the wrench
- Convex screen to magnify the torque setting scale
- Positive setting lock
- Durable & accurate
- Supplied in a durable plastic carry case



WB	□	Nm	KG
334050	9x12mm	10 - 50Nm	2.5
334051	9x12mm	20 - 100Nm	1.5
334052	14x18mm	40 - 200Nm	2.0
334053	14x18mm	60 - 340Nm	2.7

Interchangeable screen micrometer torque wrench sets

These interchangeable head torque wrench sets are part of the screen micrometer torque wrench range.

The wrench offers the operator the ability to use it as a normal 1/2" or 1/4" drive wrench, with the option of 10 or 12 metric dedicated open-end interchangeable heads.

Features:

- Accuracy +/- 4%
- Interchangeable head
- Meets or exceeds international standards
- Left & right hand operation
- Metric scale
- Metric / imperial conversion printed on the body of the wrench
- Convex screen to magnify the torque setting scale
- Positive setting lock
- Durable & accurate
- Supplied in a durable plastic carry case



Interchangeable micrometer torque wrenches

This is the interchangeable head version of the WB Tools micrometer torque wrenches. Utilising the interchangeable head option allows for a variety of combinations of open-end and 12 point ring attachments up to 1320Nm (1000ft.lbs).

Attachments are made to order. Almost any special attachment can be produced.

Features:

- Accuracy +/- 4% in both directions
- Interchangeable head
- Left & right hand operation
- Imperial & metric scales
- Positive lock with spring loaded pull down lock ring
- Super rugged knurled metal handle for industrial use
- Socket locking device
- Durable
- Meets or exceeds international standards
- Supplied with certificate of calibration
- Supplied in a plastic carry case



WB	imperial	Nm	cm	KG
376000DET	100 - 600ft.lbs	135 - 779Nm	109	6
377000DET	200 - 1000ft.lbs	305 - 1320Nm	179	15



WB	□	Nm	i	+ □	KG
334058	9x12mm	10 - 50	1/4" L&R	7mm 8mm 9mm 10mm 11mm 12mm 13mm 14mm	3.0
334060	14x18mm	40 - 200	1/2" round head	13mm 14mm 15mm 17mm 19mm 22mm 24mm 27mm 30mm	4.0