



AUSTRALIA

# REFRIGERATION



SURFACE MOUNT  
GLYCERINE FILLED



FLUSH MOUNT  
GLYCERINE FILLED



SURFACE MOUNT  
DRY CASE



FLUSH MOUNT  
DRY CASE

TYPE: SBR - Surface mount Bottom connection (back flange)  
 FRR - Flush mount Rear connection (3-hole fixing front flange)  
 PRR - Panel mount Rear connection (U-clamp fixing)

CASE: DRY - Mild Steel Case and Bezel painted Black - Dry  
 O/F - 304 Stainless Steel Case and Bezel - Glycerine Filled

DIAMETER: 100mm or 63mm

ACCURACY: 100mm +/- 1.0%, 63mm +/- 3.0%  
 of Full Scale Deflection

CONNECTION: Brass 1/4" FLARE (standard)

WINDOW: Glass

P/N Example

TYPE	CASE	DIAMETER	REFRIGERANT	HIGH or LOW
SBR	O/F	100mm	R22	H

## PRESSURE RANGES kPa

	-100	0	500	1000	1600	2000	2500	3000
R22 (L)	Blue	Blue	Blue	Blue	Blue			
R22 (H)		Blue	Blue	Blue	Blue	Blue	Blue	
R22 (HH)		Blue	Blue	Blue	Blue	Blue	Blue	Blue
R134a (L)	Blue	Blue	Blue	Blue				
R134a (H)		Blue	Blue	Blue	Blue	Blue		
OIL		Blue	Blue	Blue	Blue			
R407C (L)	Blue	Blue	Blue	Blue				
R407C (H)		Blue	Blue	Blue	Blue	Blue	Blue	
R404a (L)	Blue	Blue	Blue	Blue				
R404a (H)		Blue	Blue	Blue	Blue	Blue	Blue	Blue

Other refrigerants available on request